

MX3X



HANDHELD COMPUTERS

Voice enabled with
ToughTalk™ technology
for your voice-directed
logistics applications.

Customize the unit
with multiple endcap
options including a bar
code scanner.

Improve productivity
with full-shift Li-Ion
battery.

Polycarbonate/ABS
plastics - absorbs
impact vs. shattering
on impact.

Ten dedicated function
keys allow for one
touch application
functionality.

Compatible with RFTerm®
emulation, JAVA, & Citrix.



Large 6.5" high
visibility mono or color
display with touch
screen for crystal-clear
viewing.

Fully rugged epoxy coated
QWERTY keypad with
programmable keys makes
data entry a breeze.

With an easy in/out docking
system, the MX3X conveniently
transforms between handheld
& vehicle-mount usage -
leaving you in the driver's
seat, or free to roam your
working environment.

LXE is RUGGED RELIABLE MOBILE COMPUTERS.

Power packed unit with flexible features

The MX3X is equipped with a powerful Intel® XScale® 400MHz processor, & runs the industry standard, Microsoft® CE .NET operating system. With CE .NET, you'll gain access to Microsoft's .NET Compact Framework; loaded with smart management tools and features allowing you to personalize your computing experience.

Rugged and reliable by design

The MX3X is a fully rugged computer able to thrive in the most demanding operating conditions. You can drop it, hose it down, freeze it and still expect years of reliable service from this versatile compact computer.

And the MX3X is supported by LXE's award winning support team, winners of the Mobile Star Award™ for best customer service three years in a row.



Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal-holding.com • URL <http://www.opal.ch/> • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> • Germany • OPAL Associates GmbH • Lohnerhofstrasse 2 • D-78467 Konstanz Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opal-holding.com • URL <http://www.opalgmbh.de/> • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email info@opal-holding.com • OPAL Associates GmbH • München • Telefon +49 (0)89 12737 556 • Telefax +49 (0)89 12737 557 • Email info@opal-holding.com • OPAL Associates GmbH • Frankfurt • Telefon +49 (0)69 8236 6501 • Telefax +49 (0)69 8236 7709 • Email info@opal-holding.com • OPAL Solutions GmbH • Wilhelmstr. 22 • 52428 Jülich • Telefon +49 (0)2461 690 280 • Telefax +49(0)2461 690 284 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> • Austria • OPAL Associates GesmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opal-holding.com • URL <http://www.opalgmbh.at/> • OPAL Associates GesmbH • Donaufelderstr. 101/2/8 • 1210 Wien • Telefon +43 (0)1 270 03 13 • Telefax +43(0)1 270 03 15 • Email info@opalgmbh.at



MX3X

Technical Specifications



Processing & Memory

- Intel® XScale® PXA255 400MHz CPU
- 64MB or 128MB Flash
- 64MB or 128MB RAM

Software

- Windows® CE .NET 4.2
- AppLock® utility controls user application access & unwanted configuration changes
- Barcode wedge, RF, power mgmt & diagnostic utilities
- API's for scanner, PCMCIA, serial, battery, power management, and version control
- SDK
- Personal JAVA 1.2 JVM

Additional Software

- RFTerm® Windows CE® Terminal Emulations (VT220, TN5250, TN3270) multisession, multi-host hot-key support, with programmable function keys
- Unique keyboard overlays to match each emulation type

Keyboard

- 63 Key QWERTY format with (2) large user mappable scan keys
- 10 single touch function keys
- Phosphorescent "glowing" keys
- Epoxy coated for resistance to abrasions & chemicals

Displays & Touch Screen

- 640 x 240 1/2 VGA LCD
- 6.5" diagonal
- Fully adjustable contrast & brightness
- Resistive touch screen with anti-glare coating & tethered stylus
- Options:
 - Transmissive (Indoor) hi-bright color with double tube CCFL backlight
 - Transflective (In/Outdoor) sunlight readable monochrome w/hi-bright EL bkit

Power Supply & Management

- 10.8V, 1800mAh Li-Ion battery pack
- 8+ hour battery life with typical usage
- Battery charge time (typical)
 - 5-unit charger: 4 hours
 - Cradle: 6.5 hours
- Backup battery with automatic charging

- Power jack for external power
- Fully configurable active power management

Interfaces

- (2) RS-232 port (D9) with configurable power for external devices
- (1) USB host port (D9)
- (1) USB client port (D9)
- Integrated bar code scanner
- Infrared (IR) communications port
- Beeper with adjustable volume control
- 2.5mm audio/microphone jack
- Bluetooth tested

Expansion

- (1) PCMCIA V.2.1 slot Type I, II, III
- (1) Compact Flash Slot Type I or II

Radio Card Support - PCMCIA

- 2.4GHz 802.11b radio
- Optimized internal integrated antenna

Enclosure

- High impact polycarbonate/ABS plastic
- Available in yellow and black
- Size: 8 in. x 6 in. x 1.35 in. (203mm x 152mm x 34mm)
- Weight:
 - Monochrome 33.2 oz. (941g) including radio, battery, & scanner
 - Color 34.5 oz. (979g) including radio, battery, & scanner

Environmental

- Operating temperature range
 - Monochrome -4°F to 122°F (-20°C to 50°C)
 - Color 14°F to 122°F (-10°C to 50°C)
- Storage temperature range
 - Monochrome -22°F to 158°F (-30°C to 70°C)
 - Color -4°F to 158°F (-20°C to 70°C)
- Humidity (operating)
 - 5% to 90% RH non-condensing at 104°F (40°C)
- Drop spec: 4-ft multiple drops to concrete

- Dust & water protection enclosure rating IEC 60529 compliant to IP66
- Shock & vibration testing exceeds MIL STD 810F

Approvals

- Emissions (EMI)
 - FCC Part 15 Subpart B, Class A
 - Industry Canada ICES-003 Class A
 - EN 55022:1998, Class A
- Immunity (EMC)
 - EN 55024:1998
- Safety
 - UL 1950, CSA 22.2 No. 950, EN 60950 IEC 950
- Laser Safety
 - CDRH:21 CFR 1040.10 and 1040.11, EN 60825-1 and IEC 825-1
- Radios separately approved to FCC Part 15 Subpart C
- Industry Canada RSS 102, RSS 139 and/or 210
- R&TTE Directive: ETS 300 328, ETS 300 826, EN 60950

End Cap Options

- (2) RS-232 ports
- (1) RS-232 port with integrated bar code scanner
- (1) USB host port and (1) RS-232 port
- (1) USB client port and (1) RS-232 port
- (1) USB client port w/integrated bar code scanner
- (1) USB host port and (1) USB client port

Accessories

- 5-unit battery charger
- Vehicle cradle with power supply
- Power adapters
- Nylon cases and holsters
- Memory cards
- Desktop cradle
- Data cables
- Voice headset and carry cases

