

Digital Scanner DS 6608

Versatile Digital Scanner Future-Proofs Your Technology Investment

The DS 6608 Digital Scanner from Symbol Technologies, the Enterprise Mobility Company™, provides affordable, high-performance omnidirectional scanning of all major one-dimensional (1D) and two-dimensional (2D) bar code symbologies.

With powerful digital scanning features, the DS 6608 protects your IT investment by maximizing performance for today's applications and providing easy upgrade paths for future applications.

Innovations in Digital Scanning

User friendly for improved user productivity:

- ▶ Omnidirectional, point and shoot performance on 1D and 2D bar codes
- ▶ Five-Year Warranty
- ▶ Working range of 1-14 in./ 2.5–35.5cm on UPC/EAN symbols
- ▶ Intuitive laser generated aiming pattern
- ▶ Excellent performance on damaged or poorly printed bar codes

Cost-Effective Digital Scanning for Today's Applications

The DS 6608 Digital Scanner from Symbol Technologies is an excellent choice for your bar code scanning needs for capturing mission-critical information. The product's five-year warranty includes the exit window. In addition to advanced data capture technology, Symbol's end-to-end solutions integrate ruggedized mobile computers, wireless infrastructure, enabling software and high-ROI applications from our business partners. Symbol Enterprise Mobility Services ensure that your mobility solution works seamlessly and at maximum efficiency—from defining your business requirements through ongoing service and support.

For more information on the DS 6608 Digital Scanner, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at

www.symbol.com/ds6608



Features

Benefits

Omni-directional reading of 1D, 2D and Postal Codes	Greater productivity from one of the fastest hand-held digital scanners available
Widest working range available	Performs equally well from a distance or close-up, increasing productivity and user acceptance
Five-year warranty	Low total cost of ownership (TCO) – digital reliability
Multiple Interfaces out-of-the-box – On board	Change the host – keep the scanner
Intuitive, crisp aiming pattern	Quicker scans make the operators more productive and satisfied with the tool

DS 6608 Specification Highlights

Market: Point of Sale (POS)

Applications

1D bar codes

PDF 417 for age verification

User

Sales associate

Market: Postal

Applications

Check out

In-process operations

User

Sales Clerk

Warehouse clerk

Market: Lottery

Applications

Winning ticket verification

User

Sales Clerk

Market: Pharmacy

Applications

Reading RSS barcodes

User

Pharmacist/ Technician

Market: State and Local Government—Public safety

Applications

Citations

User

Police officer

Parking

Physical Characteristics

Dimensions:	6.55 in. H x 2.82 in. W x 4.72 in. D 16.64 cm H x 7.16 cm W x 11.99 cm
Weight (without cable):	6.04 oz./181.4 gm
Input Voltage:	5 volts +/- 10%
Operating Current:	250mA (average)
Power Sources:	Depending on host: • Host power • External power supply
Colors:	Cash Register White or Twilight Black

Performance Characteristics

Light Source:	650 nm visible laser diode
Resolution:	640 x 480
Minimum Element Width:	5 mil/0.127 mm
Nominal Working Distance:	From 1 in./ 2.5 cm to 14 in. /35 cm on 100% UPC/EAN symbols
Print Contrast:	25% minimum reflective difference
Roll (Tilt): ¹	+/- 180 degrees from normal
Pitch: ²	+/- 60 degrees from normal
Skew (Yaw): ³	+/- 50 degrees from normal
Decode Capability:	
1-D Codes:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, UCC/EAN RSS and RSS variants
2-D Codes:	PDF417, microPDF417, MaxiCode, DataMatrix (ECC 2000), Composite Codes, QR Code
Postal Codes:	U.S. Postnet, U.S. Planet, U.K. Postal, Japan Postal, Australian Postal, Dutch Postal
Interfaces Supported:	RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation, IBM 468X/469X, USB and Synapse

User Environment

Operating Temperature:	32° to 122° F/0° to 50° C
Storage Temperature:	-40° to 158° F/-40° to 70° C
Humidity:	5% to 95% relative humidity, noncondensing
Drop Specifications:	Unit functions normally after repeated 6 ft./1.8 m drops to concrete
Ambient Light Immunity:	Immune to direct exposure of normal office and factory lighting conditions, as well as direct exposure to sunlight.
Sunlight:	10,000 ft. candles/107,644 LUX
Electrostatic Discharge:	Conforms to 15 kV air discharge and 8 kV of contact discharge

Accessories

Hands-Free Intellistand™	20-66483-01, cash register white; 20-66483-02, twilight black
--------------------------	---

Regulatory


Electrical Safety:	Certified to UL1950, CSA C22.2 No. 950, EN60950/IEC950
Laser Safety:	CDRH Class II, IEC Class 2
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA

Warranty


The DS 6608 is warranted against defects in workmanship and materials for a period of 5 years (60 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty statement for details.

- 1 - Roll (Tilt): Controlled by rotating the wrist clockwise or counterclockwise
- 2 - Pitch: Controlled by dropping or raising the wrist
- 3 - Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa

1D Decode Zone for DS 6608



2D Decode Zone for DS 6608



Part No. DS6608 Printed in USA 07/04 © Copyright 2004 Symbol Technologies, Inc.
All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply.



Specifications are subject to change without notice. Symbol® is a registered trademark and The Enterprise Mobility Company™ is a trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners.

For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.

Corporate Headquarters Symbol Technologies, Inc.

One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722-6234/+1.631.738.2400
FAX: +1.631.738.5990

For Asia Pacific Area Symbol Technologies Asia, Inc.

(Singapore Branch)
Asia Pacific Division
230 Victoria Street #05-07/09
Bugis Junction Office Tower
Singapore 188024
TEL: +65.6796.9600
FAX: +65.6337.6488

For Europe, Middle East and Africa

Symbol Technologies

EMEA Division
Symbol Place, Winnersh Triangle
Berkshire, England RG41 5TP
TEL: +44.118.9457000
FAX: +44.118.9457500

For North America, Latin America and Canada

Symbol Technologies

The Americas
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722.6234/+1.631.738.2400
FAX: +1.631.738.5990

Symbol Website

For a complete list of Symbol subsidiaries and business partners worldwide contact us at: www.symbol.com

Or contact our pre-sales team at:

www.symbol.com/sales

symbol®
The Enterprise Mobility Company™

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)44 931 12 22 • Telefax +41 (0)44 931 12 20 • Email info@opal-holding.com • URL <http://www.opal.ch/> • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> • Germany • OPAL Associates GmbH • Löhnerhofstrasse 2 • D-78467 Konstanz Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opal-holding.com • URL <http://www.opalgmbh.de/> • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49 (0)4101 787 616 • Email info@opal-holding.com • OPAL Associates GmbH • München • Telefon +49 (0)89 12737 556 • Telefax +49 (0)89 12737 557 • Email info@opal-holding.com • OPAL Associates GmbH • Frankfurt • Telefon +49 (0)69 8236 6501 • Telefax +49 (0)69 8236 7709 • Email info@opal-holding.com • OPAL Solutions GmbH • Wilhelmstr. 22 • 52428 Jülich • Telefon +49 (0)2461 936 770 • Telefax +49 (0)2461 936 771 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> • Austria • OPAL Associates GesmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opal-holding.com • URL <http://www.opalgmbh.at/> • OPAL Associates GesmbH • Donaufelderstr. 101/2/8 • 1210 Wien • Telefon +43 (0)1 270 03 13 • Telefax +43 (0)1 270 03 15 • Email info@opalgmbh.at

