


Compact Series



CX Series

Convenience printing in a convenient package

Simple to use, easy to maintain and very affordable, the CX Series offers the perfect introduction to label printing. Designed for convenience, the CX Series delivers a professional labelling solution in a compact design.

- ✓ Compact
- ✓ Lightweight
- ✓ 2" + 4" print width
- ✓ 203 dpi Resolution
- ✓ 4 ips Print Speed
- ✓ Easy Loading

Convenient - Small and lightweight, the CX Series fit into the most restricted of workspaces, and can be easily moved from one area to another, from the warehouse, distribution centre, to your desk.


Easy Handling - Quick to install and easy to use, the CX Series printers are ideal entry-level label printers. Labels and ribbon are simple to load and the printer can be controlled via a PC or direct from the SATO Smart Keyboard.

Easy Printing - Complete with a start-up pack, including labels, ribbon and SATO's Dynamic Xtra label design software, you just plug n' print!

Compatible - Windows® compatible - labels can be printed directly from any Windows® applications.



DCS & Labelling Worldwide



Compact Series



CX 108

CX 208

CX 212

Printing Method	Direct Thermal only	Direct or Thermal Transfer	
Print Resolution	8 dots/mm (203 dpi)		12 dots/mm (300dpi)
Print Speed	up to 75 mm/second (3 ips)		
Max. Print Width	56 mm (2.2")	104 mm (4.1")	
Max. Print Length	1016 mm (40")	508 mm (20")	320 mm (12.6")
Media Size	Min. 19 mm (0.748") W x 9.5 mm (0.374") L	Min. 50.8 mm (2") W x 9.5 mm (0.375") L Max. 118 mm (4.65") W	
Max. Ribbon Size	108 mm (4.25") W x 140 m (459 ft.); Ink-Out		
Dimensions	140 mm W x 254 mm D x 168 mm H	175 mm W x 254 D 168 mm H (6.9" W x 10" D x 6.6" H)	
Weight	1.35 kg (2.976 lbs)	1.63 kg (3.6 lbs)	

Memory:

512k Flash/512k RAM

Media:

Roll or fan-fold labels and tags, synthetic or plain paper face stock. Centre Justified.

Max. Caliper: 0.18 mm (0.07")

Max. O.D.: 127 mm (5")

Wind: Face-In

Ribbon:

Core: 0.5" (12 mm) Internal Diameter

Sensing:

Transmissive sensor for die cut, gap and notched media. Reflective sensor for use with preprinted sensing marks. Sensor can be disabled for continuous media.

Interfaces:

- Centronics Parallel
- RS232 Serial (600 to 19,200 bps)

External Connectors:

- Parallel: 36-pin Amp
- Serial: DB-9S

Barcode Symbolologies:

Linear: UPC-A/E, EAN-8/13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet, UCC/EAN 128
2-Dimensional: PDF417, Micro PDF417, Truncated PDF417, Maxicode, Data Matrix, QR Code, RSS-14

Barcode:

2:1, 3:1, 5:2 ratio with programmable height

Human Readable Fonts:

12 proportional and mono-spaced fonts incl. OCR-A and OCR-B (code page 858, others available)

Flexibility:

360° rotation of barcodes and text, character expansion horizontally and vertically, sequential numbering, form overlay for high-speed editing of complex formats.

Graphic Support:

- SATO Hex/binary format
- PCX format

AC Power:

120V AC +10% to -15%; 50/60 Hz (std.)

230V AC +10% to -15%; 50/60 Hz (opt.)

40W Power Supply Standard

Environmental:

Operating: 5° to 40°C (41° to 104°F)

15-85% RH, non-condensing

Storage: -20° to 40°C (-4° to 104°F)

Max. 90% RH, non-condensing

ESD: 8kV

Approvals:

CE, TÜV, FCC Class A, U/L, CSA

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal-holding.com • URL <http://www.opal.ch/> • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> • Germany • OPAL Associates GmbH • Löhnerhofstrasse 2 • D-78467 Konstanz Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opal-holding.com • URL <http://www.opalombh.de/> • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49 (0)4101 787 616 • Email info@opal-holding.com • OPAL Solutions GmbH • Wilhelmstr. 22 • 52428 Jülich • Telefon +49 (0)2461 936 770 • Telefax +49 (0)2461 936 771 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> • Austria • OPAL Associates GesmbH • Voralberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opal-holding.com • URL <http://www.opalombh.at/>

